



GENERAL NOTES:

1. NO SIGN SHALL OVERHANG PRIVATE PROPERTY.
2. ANY VARIATION FROM STANDARD MUST BE APPROVED BY THE CITY OF FLORENCE.
3. LOCATE POST BETWEEN CURB AND SIDEWALK, OR BETWEEN SIDEWALK AND RIGHT OF WAY FOR CURBSIDE SIDEWALK.
4. 36" ANCHORS WITH 1-3/4" SQUARE TUBE BREAK-AWAY. VANDAL RESISTANT "DRIVE" RIVETS.
5. PUBLIC STREET SIGNS SHALL HAVE A GREEN COLORED BACKGROUND AND PRIVATE STREET SIGNS SHALL HAVE A BLUE COLORED BACKGROUND.
6. INSTALL ALL SIGNS AS NOTED ON THE CONSTRUCTION PLANS.
7. WHEN PLACED IN CONCRETE WALK, THE 4" x 4" SHALL BE PLACED IN 12" PVC PIPE WITH 3/4" ROCK COMPACTED AROUND THE 4" x 4" POST. COVER ROCK WITH 1/2" GROUT FLUSH TO WALK.

**CITY OF FLORENCE
STANDARD DRAWING**

**SIGN INSTALLATION
DETAILS**

DATE:

OCT 2012

DRAWING NO.

F-217a